Additive Manufacturing of Magnesium (Mg) Alloys

NASA

Completed Technology Project (2014 - 2015)

Project Introduction

The proposed work is to investigate additive manufacturing techniques for Mg alloys. It will leverage off research being conducted at University of Florida and Kennedy Space Center to develop these alloys and evaluate their properties.

Mg alloys as a class have higher specific strength than either steel or aluminum and offer potential for reducing weight in spacecraft. Mg has been approved by Federal and Joint Aviation standards and NASA standards state that it can be used in areas that are not prone to corrosion. Thus, the proposed applications include the skin or cladding within structural members or on non-oxidizing environments such as Mars. In addition Mg alloys can be recycled, meaning that they can be refabricated into lunar and planetary habitats.

The proposed work is to investigate additive manufacturing techniques for these alloys. It will leverage off research being conducted at University of Florida and Kennedy Space Center to develop these alloys and optimize their properties. The proposed work is designed as a one-year study to formulate an approach to use additive manufacturing to fabricate novel parts and recycle these alloys.

Mg alloys are traditionally cast then extruded and/or machined to final shape, producing many parts economically. However, these techniques are not as amenable to producing thin-gage parts and claddings proposed for space applications. Development of additive manufacturing (AM) techniques offers a novel fabrication approach, easily producing cladding and thin-gage skins as well as incorporating these alloys into compositionally-graded structures. A space-based AM system can also exploit Mg recyclability to produce lunar and planetary habitats from Mg space vehicles.

Electron beam freeform fabrication (EBF³) is an excellent candidate for AM of Mg alloys. Unlike many AM techniques using powder pre-form, its metallic wire precursor offers a much safer way to handle Mg alloys, and it naturally lends itself to the large-scale production of claddings and chemically graded parts. EBF³ is also being investigated for on-orbit and planetary use, and development of parameters for Mg production would be a large step toward the future recyclability of these materials during space exploration missions.

The aim of this project is to demonstrate the feasibility of fabricating Mg alloy structures using additive manufacturing techniques. Testing will consist of fabricating and characterizing Mg parts using LaRC's EBF³ facility.

Anticipated Benefits

Reduced cost and structural weight



Additive Manufacturing of Magnesium (Mg) Alloys

Table of Contents

Project Introduction	1
Anticipated Benefits	1
Organizational Responsibility	1
Primary U.S. Work Locations	
and Key Partners	2
Project Management	2
Technology Maturity (TRL)	2
Technology Areas	2

Organizational Responsibility

Responsible Mission Directorate:

Space Technology Mission Directorate (STMD)

Lead Center / Facility:

Langley Research Center (LaRC)

Responsible Program:

Center Innovation Fund: LaRC CIF



Center Innovation Fund: LaRC CIF

Additive Manufacturing of Magnesium (Mg) Alloys



Completed Technology Project (2014 - 2015)

Reduced cost and structural weight

Primary U.S. Work Locations and Key Partners



Organizations Performing Work	Role	Туре	Location
Langley Research	Lead	NASA	Hampton, Virginia
Center(LaRC)	Organization	Center	
• Kennedy Space	Supporting	NASA	Kennedy Space
Center(KSC)	Organization	Center	Center, Florida

Primary U.S. Work Locations	
Florida	Virginia

Project Management

Program Director:

Michael R Lapointe


Program Manager:

Julie A Williams-byrd

Principal Investigator:

Terryl A Wallace

Technology Maturity (TRL)



Technology Areas

Primary:

- TX03 Aerospace Power and Energy Storage
 - └─ TX03.1 Power Generation

 and Energy Conversion
 └─ TX03.1.5 Electrical

 Machines

